



PRODUCT DATA SHEET

Fine Finish Plaster (Setting Stuff)

RJ2.04

Description:	Non-hydraulic lime putty fine finish plaster produced from 12 month mature superfine grade Chalk lime putty mixed with fine or superfine sands at a ratio of 1: 1 by volume. Medium finish plaster also available (RJ 2.04A)
Environmental Uses:	Lime Putty plaster is an environmentally sustainable product.
Uses:	For <u>internal</u> plaster finish coats applied 2-3mm thick often in 2 coats 'wet-on-wet' over lime basecoat plasters normally after an interval of 2 or 3 days depending on temperature and humidity. Fine finish plaster is decorated with a permeable paint such as Pure or Casein limewash (RJ 3.01/RJ 3.02), or Soft or Casein Distemper (RJ 4.01/RJ 4.02) <u>Do not apply Oil-Bound Distemper (RJ 4.03) to new lime plaster.</u>
Availability:	Standard + special + matching mixes available. 15 litre tubs (c.29kgs, 35/tonne). Standard mixes are supplied ex Stock.
Shelf Life:	Unlimited. Matures and workability improves with age. Lime putty plasters stiffen during storage but can be plasticised by thorough whisking without the addition of water. Keep in original sealed tubs. Protect from frost.
Coverage:	165m ² /tonne at 3mm thick, and 250m ² /tonne at 2mm
Observations:	Tradesmen familiar with lime putty plaster, and with experience of its successful use should be employed. Lime putty plasters do not perform as gypsum, cement or hydraulic lime plasters and set by carbonation alone (the reaction with atmospheric carbon dioxide in the presence of moisture). This is a slow process and keeping moist by mist-spraying to promote carbonation, 'tending' to prevent shrinkage crazing, and protecting is crucial to success and long-term performance. Protections are essential. Do not use in excessive heat or if risk of frost.



Health & Safety:

See Health and Safety Data Sheet RJ 5.02.

CALCIUM HYDROXIDE Ca(OH)₂ Alkali (pH 13).

CAS No 1305-62-0. EINECS No 215-137-3.

Danger: H318 Causes Serious Eye Damage

Warning: H315 Causes skin irritation

Technical Data:

TAN 7	Internal Plain Lime Plastering
RJ 2.05	Use of Basecoat & Fine Finish Plasters
RJ 2.02/2.02A	Basecoat Plaster (with/without fibres)
RJ 2.04A	Medium finish plaster

Technical Advice:

From our Technical Department 01935 83676

info@roseofjericho.co.uk

Product + H & S data can be printed from our web site:

www.roseofjericho.co.uk

Disclaimer:

The information provided in this product data sheet and all technical advice is for guidance and is given in good faith but without warranty, since the site conditions and care and skill of application are beyond our control. We can accept no liability for the performance of our products, beyond the value of the material supplied. This does not affect your statutory rights.